


5-1933433-3



Modular Plug Kit, Category 6A, shielded, 8-position, 7.87 mm max cable jack OD, 100/bag

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Modular plug

General Specifications

ANSI/TIA Category	6A
Cable Type	Round, shielded
Conductor Type	Solid Stranded
Interface	RJ45
Positions/Loaded Contacts	8/8
Termination Type	IDC

Dimensions

Compatible Cable Diameter, maximum	7.87 mm 0.31 in
Compatible Insulated Conductor Diameter, maximum	1.22 mm 0.048 in
Compatible Insulated Conductor Diameter, minimum	1.12 mm 0.044 in
Contact Plating Thickness	1.27 µm
Compatible Conductor Gauge, solid	26–22 AWG
Compatible Conductor Gauge, stranded	26–22 AWG

Electrical Specifications

Insulation Resistance, minimum	500 mOhm
---------------------------------------	----------

Material Specifications

Contact Base Material	Phosphor bronze
Contact Plating Material	Gold
Material Type	Polycarbonate
Plug Shield Base Material	Brass

5-1933433-3

Plug Shield Plating Material Nickel

Mechanical Specifications

Plug Insertion Life, minimum 750 times

Environmental Specifications

Operating Temperature -10 °C to +60 °C (+14 °F to +140 °F)

Safety Standard UL 1863

Packaging and Weights

Packaging quantity 2500

Packaging Type Bag | Box | Carton